

MAXROLL-XI™

PERFECT FOR:
Large Openings
Transportation
Heavy Manufacturing
Industrial
Corrosive Environments



PERFORMAX GLOBAL
HIGH PERFORMANCE DOORS

MAXROLL-XI™

DOOR FEATURES

- Roll up door ideal for applications in:
 - Warehouses
 - Manufacturing Facilities
 - Distribution Centers
 - Corrosive Environments
- Powder-coated steel components
- Flexible bottom seal adaptable to uneven flooring
- Simple, efficient engineering providing reliability, and longevity
- High tension curtain to withstand high windloads
- **RHINOMAX™** rubber curtain with lifetime warranty



TECHNICAL SPECIFICATIONS

Opening Speed	8" per second
Closing Speed	8" per second
Max Size	50' x 35'
Drive	Direct drive VFD
Curtain	RHINOMAX™ Rubber
Guide Width	5 inches
Control Panel	NEMA-4 UL Rated
Available Curtain Colors	Black (standard) Blue, Gray (optional)
Safety Devices	Photo Eye, Electric Safety Reversing Edge, Drive Brake

OPTIONS

Mechanical	Hoods Reflective Stripes Vision
Electrical	Motor Cable Sets
Safety Devices	Wireless Safety Reversing Edge Presence Sensor Light Curtain
Activation Devices	Motion Sensors Pull Cord Push Button Remotes Floor Loops



5 Crozerville Rd, Aston, PA 19014
484.840.8500
www.performaxglobal.com